



PROFESSIONAL/FIRST RESPONDER

# EXTREME SERIES

Probably the world's most extreme fire blanket





**BRIDGEHILL®**  
WE SIMPLY BLOCK FIRE

PROFESSIONAL/FIRST RESPONDER

## EXTREME SERIES



For instruction videos  
scan QR code



### Product information

- Isolate and extinguish small fires
- Blocks any fire, even small lithium battery fires
- Multipurpose
- Immediately isolates toxic gases and smoke, protecting civilians from carcinogen exposure
- Comes in a smartbag
- Requires no maintenance
- Metal chain integrated to add weight for easier use

### Ideal for:

Battery fires - Restaurant kitchens – Industry tools – The recycling industry  
– Car manufacturers – Workshops – Shops or businesses that store small or large amounts of lithium batteries – Battery manufactores- Marine - Aviation - Military



### Small:

± 4.9 x 4.9 ft  
± 13.2 lb

### Medium:

± 9.8 x 9.8 ft  
± 39.6 lb

### Large:

± 13 x 13 ft  
± 106 lb

### How to use

Handled by:

1. Take the fire blanket out of the smartbag.
2. Gently cover the burning object.
3. Make sure the fire blanket is tight all the way around the burning object. Wait at least 20 minutes.

For fire in electric scooters/  
tools etc. Wait for firefighters to  
assess the situation further!



**ALWAYS CALL THE  
FIRE DEPARTMENT!**



BRIDGEHILL®  
WE SIMPLY BLOCK FIRE

TECHNICAL SHEET

EXTREME SERIES

PROFESSIONAL/FIRST RESPONDER			
SKU:	Extreme Small: 504210    Extreme Medium: 504211    Extreme Large: 504213		
Sizes/Weight:	<b>Small:</b> ± 4.9 x 4.9 ft ± 13.2 lb	<b>Medium:</b> ± 9.8 x 9.8 ft ± 39.6 lb	<b>Large:</b> ± 13 x 13 ft ± 106 lb
Core material:	Total six layers solution. Two layers of Pyroxene.		
Coating:	± 550 gsm silicone. Four layers of BridgeTech™ coating. In fires with high levels of conduction heat, flames may appear from the coating of the fire blanket. This will not alter the performance of the fire blanket.		
Egde on blanket:	Metal chain sewed in aorund the egdes to add weight.		
Main usage:	Blocks any small fire, even lithium battery fires.		
Smartbag:	Airtight bag. Use silicon grease on the zipper to keep the bag airtight.		

Technical specification:

Core Fabric			Unit	Tolerance
Yarn	Warp Weft	300 165	Tex Tex	± 5 ± 5
Yarn count	Warp Weft	8 8	Ends/cm Ends/cm	± 5 ± 5
Tensile strength	Warp Weft	3200 2500	N/50mm N/50mm	≥ ≥
Area weight	–	1200	G/m2	± 10%
Thickness	–	0.40	Mm	± 5%
Weave pattern	–			4H satin
Service temperatures on core fabrics	Short term ± 2912 °F Long term ± 1472 °F			

